



# WIFI ACCESS CONTROL KEYPAD

INT1KPWF



## KEY FEATURES

- Up to 988 users
- IP66 weather resistant
- Multiple Access Modes: Smartphone, Card, PIN code, Fingerprint
- Remotely access & unlock via app
- Add/ Delete users by app
- Temporary Password (One-time Or Period Code)
- Metal housing, anti-vandal
- Programmable time restriction for users
- Support checking Opening Record
- 12-18VDC Power *(power supply not supplied)*



## IntelLink App

Free App provided, support remote viewing on iOS or Android™



FIRE • SECURITY • INTERCOMS

17 Millicent Street, Burwood, VIC 3125 Australia  
Tel: 1300 PSA PRODUCTS (1300 772 776)  
Fax: (03) 9888 9993  
enquiry@psaproducts.com.au

psaproducts.com.au





Model	INT1KPWF
User Capacity	Hardware User: 1000 / APP User: 500
Common User	100 Finger+ 888 PIN/Card Users
Visitor User	10
Panic User	2
PIN Length	4-6digits
Operating Voltage	12-18V DC (power supply not supplied)
Idle Current	<60mA
Active Current	< 150mA
Proximity Card Reader	EM and Mifare
Radio Technology	125KHz/13.56MHz
Read Range	2-6cm
Wiring Connections	Relay output, exit button, alarm, door contact, Wiegand input/output
Relay	One (NO, NC, Common)
Adjustable Relay Output Time	0-99 Seconds (5 seconds default)
Lock Output Load	2 Amp Maximum
Wiegand Interface	EM card version: Wiegand 26-44 bits input & output (Factory default: Wiegand 26bits) Mifare card version:Wiegand 26-44 bits,56bits,58bits input & output (Factory default: Wiegand 34bits) 4 bits,8bits (ASCII), 10 digits Virtual Number(Factory default:4bits)
Environment	Meets IP66
Operating Temperature	-30° C - 60° C (-22° F -140° F)
Operating Humidity	0%RH-98%RH
Physical	Zinc-Alloy
Color	Sliver & Black
Dimensions	L148 x W43.5 x H22 (mm)
Unit Weight	330g
Shipping Weight	405g

FIRE • SECURITY • INTERCOMS